

Special transport permit conditions 5/2025

These permit conditions must be kept with the transport.

In effect from 2 January 2026

These conditions include the most important points of the provisions and regulations concerning special transport and the permit conditions set for special transport. A permit-specific special condition must be observed in special transports even when new provisions and regulations are in force. In these permit conditions, references to the Finnish Transport and Communications Agency Traficom's special transport regulation are indicated with the word Traficom and a numerical reference to the section of the regulation, and the Road Traffic Act is abbreviated as RTA and the Vehicles Act is abbreviated as VA. Economic Development Centre of Inland Finland grants all special transport permits in Finland with the exception of Åland.

1 General conditions (Traficom 1, 3 RTA sections 159, 181, 182, 191, VA sections 38, 146, 147)

A vehicle used for special transport must be approved for traffic in accordance with the provisions of the Vehicles Act. A vehicle is approved for traffic if it meets the requirements set for a vehicle used in traffic. It is prohibited to exceed the mass limits permitted by the special transport permit and approved for traffic or the mass limits set for a coupled combined vehicle. When a trailer that exceeds the dimensions or mass generally permitted on the road is coupled to a towing vehicle, the coupling has to be approved by a coupling inspection.

The special transport permit is only valid on the route(s) indicated in the permit. The general provisions concerning vehicles on the road apply to a transport that is off-route. In roadside inspections, the dimensions and mass numbers of the transport must be in the same transport permit.

The special transport permit or a copy thereof, including its appendices, and up-to-date valid permit conditions must be kept with the transport and, if required, presented immediately to a traffic controller. A transport permit and the permit conditions are also valid in electronic format, provided that the electronic version can be read at a controller's inspection point. The route description is not considered a copy of the permit if the permit or a copy thereof and its appendices are not presented to the controller. In addition to the police, traffic controllers include customs and border authorities.

A special transport permit can be cancelled temporarily or permanently if the permit holder does not follow special transport provisions or regulations or the conditions set in the special transport permit, or if the permit conditions are no longer valid.

2.1.2026

2 Other permits

2.1 Municipalities and private roads

As a rule, a special transport permit includes consent to the use of streets and private roads, but the permit authority may require the permit holder to obtain information from the party responsible for road maintenance that a street or private road mentioned in the permit can be used. The permit holder cannot independently supplement the special transport permit to include streets or private roads of their choice; a special transport permit must be applied for from the permit authority.

3 Constraints on transport

3.1 Road structures

If the transport requires any modifications of road structures or roadside equipment, permission must be obtained from the party responsible for the maintenance of the road before the transport. Such modifications include, for example, lifting portals, detaching electrified traffic control devices and lampposts, removing railings, making changes to intersections, constructing ramps to cross traffic islands, and strengthening the road structure. Economic Development Centre of Inland Finland grants permits for road work on highways. Permits for road work on road networks and private roads must be obtained from the party responsible for the maintenance of the road. Any work and alteration permits must be applied for well in advance of the time of transport.

Traffic signs and traffic control installations that are not electric can be temporarily removed without the permission of the party responsible for road maintenance, provided that the work does not require the use of machinery and the signs and installations are immediately returned to their place upright and facing the right direction.

Lifting portals requires following the portal work guidelines. A special transport permit and the portal work guidelines do not justify lifting or detaching a portal.

In the case of retractable bollards, the bollards must be removed and reinstalled if there is a risk of the transport damaging a bollard. A retractable bollard may be removed up to 2 hours before the transport, and it must be reinstalled no later than 2 hours after the transport. If a bollard is damaged during transport, the permit holder is responsible for notifying the Road User's Phone Service at 0200 2100 and for compensating the costs of breaking the bollard.

3.2 Railway level crossings

At railway level crossings, special transports must comply with the Finnish Transport Infrastructure Agency's guideline on special transports at level crossings (VÄYLÄ/1484/06.04.01/2021, Transport Infrastructure Agency Guidelines 8/2021 v3).

3.3 Tram lines

When a transport over 4.8 m tall crosses the tramway in Helsinki (the Raide-Jokeri express track), Metropolitan Area Transport Ltd must be contacted at least fourteen (14) days before the transport takes place.

2.1.2026

When crossing the Raide-Jokeri express track in Helsinki and Espoo, transports over 5.5 metres tall (over 5.1 metres tall in the Hevoskenenkä junction areas in Leppävaara, Espoo) Metropolitan Area Transport Ltd must be contacted for instructions at least fourteen (14) days before the transport takes place. For more information and contact information, see <https://kaupunkiliikenne.fi/kaupunkiraidehankkeet-ja-kunnossapito/urakoitsijalle/tyot-raitiotieradan-laheisyydessa/>.

When a transport over 5.0 metres tall crosses the tramway in Tampere, Tampereen Raitiotie Oy must be contacted at least seven days before the transport. For more information and contact information, see <https://www.tampereenratikka.fi/ammattilaisille/erikoiskuljetukset/>

3.4 Power lines and telephone cables

Before transport, the special transport permit holder must investigate the heights of power lines and telephone cables and, if necessary, agree with the owners of the lines and cables on the measures required for the transport.

3.5 Road works

The special transport permit holder must investigate any road works in progress on the route and take into account their impacts on the transport.

3.6 Weight limits

The weight limits indicated by traffic signs must be complied with if the special transport permit does not grant specific exceptions. The route indicated in the special transport permit is not a specific exception of this kind.

3.7 Vehicle position on the road

Special transports should avoid using road edges. On motorways, semi-motorways, wide lane sections and in places with at least two adjacent parallel lanes, using the road edges is not allowed at bridges unless otherwise specified in the permit.

4 Liability for costs and damages (RTA sections 158, 184, 191)

Special transports must take special care and account for road and weather conditions so that the hazards and inconvenience caused by the transport are adequately prevented. If necessary, the supervisory authority, the party responsible for road maintenance and the permit authority can restrict the movement of a transport on a road.

Normal road maintenance measures are the responsibility of the party responsible for maintaining the road. Gritting, ploughing or similar measures to be carried out upon request of a special transport operation are subject to a fee for the special transport permit holder and must be requested well in advance.

Lifting, removing and re-installing portals and control devices are done at the expense of the special transport permit holder.

2.1.2026

Before transportation, the availability of a special transport permit for the transport in question must be ensured. For example, road repairs and the construction of underpasses may restrict or prevent a transport entirely. A special transport permit is not an assurance that unobstructed transport is possible; it is a permit to use the road network in a manner that would otherwise be prohibited.

The holder of a special transport permit or the party doing the transport is liable for damage caused by the special transport to the road, green areas and their and structures, traffic control equipment, road markings, snow stakes and other road equipment and structures, such as bridges. Provisions on liability for damages are contained in the Tort Liability Act (412/1974).

The permit holder must immediately notify the Road User's Phone Service at 0200-2100 if a special transport damages road equipment and structures or if a removed traffic control device cannot be re-installed. If problems with special transport occur in the Oulu region, the transport must contact Tampere Road Traffic Centre, tel. 020 637 3235.

5 Loading (Traficom 4, RTA section 158)

When loading an indivisible object, the primary aim must be to reduce the width of the transport and, secondarily, the height.

Multiple indivisible objects may only be loaded onto a vehicle or a combined vehicle if the indivisible objects exceed the generally permitted height, width or length on the road even when loaded as singles. The dimensions generally permitted on the road may not be exceeded by placing objects on top of each other, side by side or after one another. Generally permissible mass limits may not be exceeded by a load with several indivisible objects.

Other items may be loaded with an indivisible object provided that the load consisting of the other items does not exceed the generally permitted height and width on the road. The other load must be loaded in such a way that it does not exceed the overall length of cargo space generally permitted on the road for an equivalent vehicle or combined vehicle. Loads such as these may not exceed the generally permitted mass limits on the road.

6 Warning measures and related equipment (Traficom 5, 6, 7, RTA sections 65, 66, 67, VA section 19)

6.1 Warning measures

The minimum requirement for traffic control and warning vehicles is determined by the dimensions of the transport. When using two or more warning vehicles, one warning vehicle must be behind the transport and the others in front of the transport. On motorways and other roads where there is no oncoming traffic, the warning vehicle(s) are placed behind the transport. If necessary, a special transport permit may require the use of warning measures that are above the minimum.

2.1.2026

Minimum number of warning vehicles and EKL controllers in special transport						
	Width (m)					
Length (m)	max 3.00	over 3.00	over 3.50	over 4.00	over 5.00	over 7.00
max 30.00			1	2	3	4
over 30.00	*)	1	1	2	3	4
over 35.00	1	2	2	3	3	4
over 40.00	2	2	3	3	3	4
over 45.00	2	3	3	3	3	4
over 50.00	3	3	3	3	3	4

*) A warning vehicle must be used if the width of the transport exceeds 2.60 metres and the length exceeds 30.00 metres and the combined vehicle does not meet the manoeuvrability requirement laid down in section 132 of the Road Traffic Act when unladen.

An EKL vehicle must be used as a warning vehicle if the transport width exceeds 4.00 metres or the length exceeds 40.00 metres.

In addition, a warning vehicle must be used if

- the longitudinal distance from the rearmost axle of the vehicle or combined vehicle to the rearmost point of the vehicle or load is more than 6.00 metres and the vehicle or combined vehicle, if laden, does not meet Traficom's manoeuvrability requirements.
- the transport uses the oncoming lane or when the vehicle is primarily in the lane of oncoming traffic
- driving over the centre line of the roadway, excluding
 - a) intersections
 - b) driving into a curve where the vehicle partly crosses the centre line of the road when turning
 - c) roadways or parts of roadways that are less than 5.70 metres wide
 - d) exceptional arrangements for roadwork or an accident
 - e) turning against the direction of turn indicated by a traffic sign
- the vehicle or combined vehicle
 - does not meet Traficom's manoeuvrability requirement when unladen
 - exceeds the lateral displacement dimension of 1.70 metres specified by Traficom when laden.
- the maximum permitted speed for the transport is under 40 km/h
- the height of the special transport is over 5.00 metres; a warning vehicle is not required when the transport follows the route specified in the special transport permit and the carrier has ensured that a warning vehicle will not be necessary to measure the height of structures above the road.

2.1.2026

An EKL controller must be used during a special transport if

- the transport requires the use of an EKL vehicle or warning vehicle as described above
- the transport requires stopping other traffic
- the transport is a part of a consecutive group of special transports
- the load prevents the driver from the rear or side of the transport either directly or by means of a device enabling an indirect view

6.2 Warning vehicle

A warning vehicle may be a passenger car, van or truck with a maximum mass of 7.5 tonnes without a trailer.

The specific requirements for a warning vehicle are specified in chapter 6.1 of the special transport regulation.

6.3 EKL vehicle

An EKL vehicle must meet the requirements for a warning vehicle. The main colour of an EKL vehicle must be signal yellow, golden, traffic yellow or similar. The vehicle's register data must include a mention on approval as an EKL vehicle.

The specific requirements for an EKL vehicle are specified in chapter 6.3 of the special transport regulation.

6.4 Warning signs

Warning signs are used on warning vehicles and EKL vehicles. Warning signs are used so that the primary warning concerns the width of the transport, the secondary warning concerns its length and the third concerns the height of the transport.

The lower edge of the warning sign shall be at a height of at least 1.70 metres, and the sign must be at least 1000 millimetres wide and 500 millimetres high. It has to read ""LEVEÄ" (wide), "PITKÄ" (long) or "KORKEA" (high) on the upper half of the warning sign. On the lower half of the sign, it can read "KULJETUS" (transport), "BRED", "HÖG", "LÅNG", "WIDE", "HIGH" or "LONG" or feature an illustrative symbol or other information related to the transport. The warning sign may have an electronically modifiable display.

A warning sign approved before 5 May 2025 may still be used or changed to comply with Traficom's special transport regulation without changing the dimensions of the warning sign. New warning signs must meet the requirements of Traficom's special transport regulation.

6.5 Warning lights

Warning lights must be used when a transport does not follow the rules of the road or if warning other traffic is necessary in order to avoid apparent danger. When the transport is following the rules of the road, warning lights shall not be used solely for over-high loads or the towing vehicle of an over-long load or the warning vehicles used in the front. Warning

2.1.2026

lights must be used for the entire duration of the transport in the warning vehicles or EKL vehicles at the back.

6.6 Free height measuring device

The measurement is mainly used when the transport height exceeds 5 metres. In repeated transports on the same route, measurement is not necessary if the usability of the route for the transport has been ensured by other means without damaging road equipment.

6.7 Traffic controller for special transport (EKL controller)

Only persons authorised to control traffic for special transports may act as traffic controllers for special transport. The EKL right is proven with an EKL card. The traffic controller must hold category B driving rights. The driver of the special transport vehicle may not act as the traffic controller.

An EKL controller must always be used when a transport requires stopping traffic, if an EKL vehicle or a warning vehicle is required or if the transport is part of a consecutive group of special transports. the number of EKL controllers used in a special transport must at least match the minimum number of warning vehicles.

6.8 Communication tools

The drivers of warning vehicles or EKL vehicles and special transport vehicles must have a radio or telephone connection and a shared language for communication.

6.9 Traffic controller's outfit

The traffic controller's outfit must be visible. The warning clothing must meet the requirements of SFS-EN 471 / SFS-EN ISO 20471 class 3 or higher.

6.10 Stopping traffic

To stop other traffic, a miniature “closed to all vehicles” (C1) traffic sign (\varnothing 200 or \varnothing 400 mm) must be used. When it is dark or when visibility is otherwise limited, an equivalent lit up sign must be used (\varnothing 200 or \varnothing 400 mm). (Government Decree on the Use of Traffic Control Devices 379/2020, section 34)

6.11 Senior traffic controller

Where several traffic controllers are involved, one of them must act as senior traffic controller. The location of traffic controllers is determined by the senior traffic controller or the police.

7 Groups of special transports (Traficom 7.5.)

Special transports may be arranged as groups of up to four special transports. If there are several special transport groups in traffic, they must be driven 5 minutes apart at minimum. the minimum number of EKL vehicles, warning vehicles and EKL controllers in a group is:

- a) as many as is necessary for the largest transport of the group when transporting alone;
- b) one in front of the group and one behind the group; however, in the case of a group of two or three transports, one if the widths and lengths of all the transports are within what is generally permitted on the road;

2.1.2026

- c) in a group of four transports, one after two transports if at least one of the transports exceeds the width or length that is generally permitted on the road;
- d) one in front of and behind each transport over 6.00 metres wide or over 40.00 metres long.

When crossing bridges, the transports in a special transport group have to cross one at a time. The following transports may cross a bridge one at a time only when the previous one has crossed the bridge.

8 Speed (Traficom 3.2, 8)

The speed of a special transport may not exceed 60 km/h if the transport or part of the transport is in the oncoming lane or a part of the oncoming lane. The speed of excess mass transports is limited by the mass placed on the tyres and axle of the vehicle in accordance with Traficom's regulation. However, the transport may not exceed the speed generally permitted for a transport vehicle on the road, the speed entered for the vehicle in the register or the speed indicated by a traffic sign.

9 Time and road condition restrictions for transport

Transports over 4 metres wide, over 34.5 metres long or over 5 metres tall are prohibited:

- Monday through Friday, from 6:00 to 9:00 and from 15:00 to 17:00. The restriction stands on highway 25 and main road 55 as well as on state-owned highways, main roads and regional roads encompassing them and also on the ring and bypass roads in Turku, Tampere, Lahti, Joensuu, Jyväskylä, Kuopio and Oulu.
- The time restrictions apply during the specified time periods, including on municipal road networks covered by the special transport permit in the municipalities mentioned above, as well as in Helsinki, Espoo and Vantaa.
- In the above-mentioned restricted hours and areas in the summer (from 1 May to 31 August) on Fridays and Sundays from 15:00 to 20:00.
- On motorways, the restricted hours apply to all transports with a maximum permitted speed of 60 km/h or less.
- In the vicinity of major public events (e.g. World Rally Championship, Conservative Laestadians' Summer services, housing fairs, the Finnhorse Trotting Championship, festivals with more than 50.000 visitors) during each event.
- In addition to the above, on the eve of Midsummer, Christmas and Good Friday or on the last day of consecutive holidays between 15:00 and 20:00. The restriction applies throughout the country on highways and main roads.
- In areas with a warning of very poor driving conditions (<https://liikennetilanne.fintraffic.fi/kartta/>).

The time restrictions do not apply to unladen combined vehicles on state-owned roads or on municipal road networks.

The police may, for a justified reason, grant a permit to deviate from the restricted hours and specify when a transport may be undertaken.

2.1.2026

10 Markings on a special transport (Traficom 5, 11)

A load does not need to be marked in accordance with Traficom's special transport regulation if

- a) the load does not exceed the width of vehicles generally permitted on the road on one or both sides by more than 0,10 metres;
- b) the load does not exceed the width of the vehicle on one or both sides by more than 0.10 metres;
- c) the load does not exceed the length of the vehicle by more than 1.00 metres in front of the vehicle or 2.00 metres at the back of the vehicle.

More detailed instructions for marking loads are specified in sections 5 and 11 of Traficom's special transport regulation.

11 DIMENSIONS ALLOWED IN SPECIAL TRANSPORT WITHOUT A SPECIAL TRANSPORT PERMIT (Traficom 9, RTA sections 125, 126)

A special transport permit is required if a transport significantly exceeds a dimension generally permitted on the road. However, a special transport permit is not required if vehicles registered or put into service in an EU or EEA Member State are used for the transport and if the width or length of the vehicle or combined vehicle used for transport, when loaded or unladen, does not exceed the dimensions given in the table below.

The generally permitted height on the road is 4.40 metres for EU and EEA state vehicles.

Vehicle, combined vehicle and load	Width (m)	Length (m)
lorry and semi-trailer combination	4.00	40.00
combination of lorry and the trailer proper or combination of lorry and several trailers ¹⁾	4.00	30.00
combination of tractor and unladen peat production trailer or tractor and towed device	4.00	30.00
tractor and trailer combination	4.00	20.00
tractor and vehicle transport trailer combination	3.50	20.00
self-propelled vehicle that is not primarily intended for carrying load	4.00	20.00
lorry ^{2, 3)}	4.00	13.00
vehicle transport vehicle	3.50	16.00
van	3.50	13.00
vehicle and centre axle trailer combination ⁴⁾	3.50	20.75

¹⁾ The length of a lorry and trailer combination or combination of lorry and several trailers is however up to 34.50 m when up to 3.50 m wide

²⁾ The length of 13.00 metres may be exceeded when the load carried on a trailer is moved during loading or unloading by a truck with a crane suitable for loading

³⁾ However, when transporting boats, the length of the lorry is 16.00 metres

⁴⁾ The length of a lorry and towed device combination is however 30.00 metres

12 Applied acts and regulations

Road Traffic Act (RTA) 729/2018

Vehicles Act (VA) 82/2021

Tort Liability Act 31.5.1974/412

Technical requirements for vehicles and their trailers (vehicle regulation)

TRAFCOM/422611/03.04.03.00/2020

Special transports and special transport vehicles (special transport regulation)

TRAFCOM/621106/03.04.03.00/2023

Structure and equipment of tractors, motorised work machines and off-road vehicles, their trailers, devices intended for towing machines other than cars, and vehicles for transporting animals (tractor regulation) TRAFICOM/75637/03.04.03.00/2020.

Special transports at level crossings VÄYLÄ/1484/06.04.01/2021

Government Decree on the Use of Traffic Control Devices 379/2020